



6.8	40.6	38	42	2X20
6.8	38.6	36	40	2X19
6.8	36.6	34	38	2X18
6.8	34.6	32	36	2X17
6.8	32.6	30	34	2X16
6.8	30.6	28	32	2X15
6.8	28.6	26	30	2X14
6.8	26.6	24	28	2X13
6.8	24.6	22	26	2X12
6.8	22.6	20	24	2X11
6.8	20.6	18	22	2X10
6.8	18.6	16	20	2X09
6.8	16.6	14	18	2X08
6.8	14.6	12	16	2X07
6.8	12.6	10	14	2X06
5.1	10.6	8	12	2X05
D	C	B	A	CKT.

SPECIFICATIONS

Current Rating: 3A AC, DC
 Voltage Rating: 250V AC, DC
 Temperature Range: -25c ~ +85c
 Contact Resistance: 10mΩ Max.
 Insulation Resistance: 1000MΩ Min.
 Withstanding Voltage: 800V AC/minute
 Material: Nylon 66, UL94V-0
 Color: Natural (White)

东莞市钰茂实业有限公司

TEL:0769-87903290 FAX:0769-87864246

Angle	± 0.5°	品名	PITCH 2.0mm HOUSING			
10.0 ~	± 0.20	TITLE:				
3.1 ~ 10.0	± 0.10	料号	A2012H			
1.1 ~ 3.0	± 0.05	PART NO.				
0 ~ 1.0	± 0.03	绘图	Simon	审核	Jeff	核准
UNIT: mm		DRAWING	CHECKED	APPROVED		
A4		日期	18.12.01	比例	FREE	版本
		DATE	SCALE:	REV.		V1.0